



EXCEED EN 857 – 2SC

Part No.	DN	Nominal ID		Nominal OD		Working Pressure		Min. Bend Radius		UOM
		mm	In.	mm	In.	BAR	PSI	mm	In.	
EHP-1/4"	6	6.4	0.25	14.2	0.56	450	6,525	33	1.3	Meter
EHP-5/16"	8	7.9	0.31	16	0.63	400	5,800	38	1.5	Meter
EHP-3/8"	10	9.5	0.38	18.3	0.72	400	5,800	42	1.65	Meter
EHP-1/2"	12	12.7	0.5	21.5	0.85	360	5,220	60	2.36	Meter
EHP-5/8"	16	15.9	0.62	24.7	0.97	350	5,075	68	2.68	Meter
EHP-3/4"	19	19	0.75	28.6	1.13	330	4,785	80	3.15	Meter
EHP-1"	25	25.4	1	36.6	1.44	280	4,060	150	5.9	Meter
EHP-1.1/4"	31	31.8	1.25	44.3	1.74	172	2,500	210	8.27	Meter
EHP-1.1/2"	38	38.1	1.5	52.8	2.08	138	2,000	250	9.84	Meter
EHP-2"	51	50.8	2	65.5	2.58	110	1,600	315	12.4	Meter

Tube :

- Synthetic Rubber , resistant to hydraulic fluids.

Reinforcement :

- Two braid of high tensile steel wire.

Cover :

- DURA TUFF Synthetic , MSHA Approved,

Temperature Range (Medium) :

- -40° C to 126° C